



i3LE & i4

# **SCANIA IRIZAR**

Based on solid engineering experience, our new generation of buses has been developed to meet the demands of today's and tomorrow's cities. Energy efficient and available in a wide range of powertrains, it offers the latest technology in everything from safety systems to reduced emission and noise levels. And through excellent uptime and fuel economy, Scania Irizar buses allow sustainable mobility to go hand-in-hand with operating economy.



#### General

Wheel configuration: 2-axle, 3-axle with steered tag axle

Door configuration:

i3LE: 1-2-0, 2-2-0 i4: 1-1-0. 1-2-0

#### **Dimensions**

#### Lenath:

i3LE: 10.95 m, 12.0 m, 12.75 m (2-axle) 14.0 m, 14.9 m (3-axle) i4: 10.8 m, 12.2 m, 12.9 m (2-axle) 14.0 m, 15.0 m (3-axle)

Width: 2.55 m

#### Height:

i3: 3.399 m i4: 3.405 m

May vary depending on the market, powertrain and configuration.

# Passenger area

Seating: Irizar seats as standard or customer choice, manual or automatic wheelchair lift at the middle door or manual in front door, four priority seats with folding armrests, location for wheelchair or pram, folding seats, reading lamp and air nozzles

**Equipment:** Luggage rack, camera surveillance, infotainment system (Wi-Fi), interior LED or fluorescent lighting

Roof hatches: Electric or fixed

#### **Driver area**

Seating: Heated driver seat ISRI

Instrument panel: Adjustable or fixed

Support systems: Scania Driver Support, electro-pneumatic parking brake, adaptive cruise control, vulnerable road user collision warning, blind spot warning, lane departure warning, hill-hold

Equipment: Audio system, announcement system

# **Destinations signs**

Placement: LED destination sign in front, side and rear

# Climate system

**Heating and cooling:** Convector circuit in passenger area, auxiliary heater (diesel or gas), defroster, separate or combined air conditioning for the driver, temperature-controlled ventilation and AC for passengers

# Powertrain - Hybrid electric (biodiesel, HVO, diesel)

9-litre engine 320 hp (235 kW), torque 1600 Nm Electric motor 320 hp (130 kW), torque 1030 Nm

Gearbox: 12-speed with Scania Opticruise

## Powertrain - Combustion, Euro 6

# Biodiesel, HVO, diesel:

7-litre 280 hp (206 kW), torque 1200 Nm 9-litre 320 hp (235 kW), torque 1600 Nm 9-litre 360 hp (265 kW), torque 1700 Nm

#### HVO, diesel:

9-litre 280 hp (206 kW), torque 1400 Nm 13-litre 370 hp (272 kW), torque 1900 Nm

#### Fuel capacity:

140-400 litres

#### Biogas, natural gas:

9-litre 280 hp (206 kW), torque 1350 Nm 9-litre 340 hp (250 kW), torque 1600 Nm

Fuel capacity: 1260-1875 litres

#### Gearbox:

12-speed with Scania Opticruise

6-speed fully automatic with acceleration control

# Powertrain - Combustion, Euro 5

### Biodiesel, HVO, diesel:

9-litre 280 hp (206 kW), torque 1400 Nm 9-litre 320 hp (235 kW), torque 1550 Nm 9-litre 360 hp (265 kW), torque 1700 Nm

# Powertrain - Combustion, Euro 3

#### Biodiesel, HVO, diesel:

9-litre 250 hp (184 kW), torque 1250 Nm 9-litre 310 hp (228 kW), torque 1550 Nm  $\,$ 

# **Electrical system**

**Equipment:** Halogen or bi-xenon headlights, Bi-LED, LED daytime running, position and indicator lights, LED side and rear lights
Battery 150 Ah, 180 Ah, 230 Ah or dual battery system
Alternator 150 A, 180 A, 2x150 A or 2x180 A

# Brake and safety equipment

Equipment: Disc brakes, electronic brake system (EBS), anti-lock brake system (ABS), traction control (TC), integrated retarder, bus stop brake, rear view camera, fire extinguishing equipment in the engine compartment

# Suspension and wheels

Front suspension: Independent or rigid, kneeling front door, whole front or whole side, automatic or manual control, total raising and lowering

Rims: Aluminium or steel

# Tyres:

Low entry: 275/70, 275/80, 295/80, 305/70, 315/60, 315/70 (front) 275/70, 275/80, 295/80, 305/70, 315/60, 315/70, 315/80 (rear) 275/70, 275/80, 295/80, 305/70, 315/60, 315/70, 315/80, 385/65 (tag) High floor: 275/70, 275/80, 295/80, 305/70, 315/60, 315/70, 385/65 (front) 275/70, 275/80, 295/80, 305/70, 315/60, 315/70, 315/80 (rear) 275/70, 275/80, 295/80, 305/70, 315/60, 315/70, 315/80, 385/65 (tag)

# Doors and windows

**Optional:** Tinted windows, single or double-glazed side windows, double doors, inswing or sliding, doors at customer's choice